NSN 5915-00-166-1387

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-166-1387

Overall Height:
2.750 inches
Body Length:
1.812 inches
Body Width:
1.250 inches
Body Height:
2.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Reference Frequency Per Function:
110.0 hertz blank
Input Impedance Per Function W/load:
2.0 kilohms blank
Output Impedance Per Function W/source Across Input:
2.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Hermetically sealed Mounting Facility Type And Quantity:
•
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size: 0.138 inches
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size: 0.138 inches Body Material:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size: 0.138 inches Body Material: Metal
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function:
Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Specified Frequencies Of Discrimination Per Function: 80.00 hertz blank and 140.00 hertz blank and 240.00 hertz blank and 500.00 hertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function: 80.00 hertz blank and 140.00 hertz blank

Tin

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-166-1387

Low Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0