

View Online at <https://aerobasegroup.com/nsn/5915-00-166-6023>

**Vibration Resistance Range In Hertz:**

+16.0 to 25.0

**Operating Temperature Range:**

-25.0 to 45.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

60.0 kilohertz blank

**Source Impedance Rating Per Function:**

10.0 kilohms blank

**Load Impedance Per Function:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

36.00 kilohertz blank and 56.50 kilohertz blank and 63.50 kilohertz blank and 84.00 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

56.50 kilohertz blank and 63.50 kilohertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0