NSN 5915-00-167-4806

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-167-4806

Overall Length:

8.190 inches

Body Outside Diameter:

0.440 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.750 inches

Operating Tempurature Range:

-28.0 to 65.0 degrees celsius

Reference Frequency Per Function:

400.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

388.00 megahertz blank and 412.00 megahertz blank and 500.00 megahertz blank and 900.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

388.00 megahertz blank and 412.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 40.0 blank and 40.0 blank

Special Features:

Unthreaded holes in mounting brackets

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5915-00-167-4806

Low Pass Filter - Page 2 of 2

Demilitarization:

No

Fiig:

A047b0

