## NSN 5915-00-167-6926

High Pass-low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-167-6926 **Overall Length:** 2.937 inches **Overall Height:** 2.281 inches **Body Length:** 2.687 inches **Body Width:** 1.468 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.937 inches **Vibration Resistance Range In Hertz:** +2.0/+50.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.937 inches **Operating Tempurature Range:** -55.0 to 85.0 degrees celsius Average Life Rating In Hours: 10000.0 **Source Impedance Rating Per Function:** 10.0 kilohms single low pass 2nd function **Load Impedance Per Function:** 10.0 kilohms single low pass 2nd function **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 4 threaded stud 1st function Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 single low pass 2nd function **Functional Terminal Type And Quantity:** 2 wire hook output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 100.0 volts at altitude **Thread Size:** 0.112 inches **Body Material:** Metal

**Style Designator:** 

Rectangular terminal/terminals on adjacent surfaces

## **Test Data Document:**

18876-10237097 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## NSN 5915-00-167-6926

High Pass-low Pass Filter - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0