

View Online at <https://aerobasegroup.com/nsn/5915-00-169-2349>

Overall Length:

5.232 inches

Body Length:

3.937 inches

Body Outside Diameter:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

420.0 blank

Operating Current Rating Per Function In Amps:

5.0 blank

Maximum Voltage Drop Per Function:

750.0 millivolts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.15 and 100.0 and 1000.0 and 10000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

75.0 and 75.0 and 60.0 and 60.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing 3rd function

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

150.0 volts at sea level

Operating Voltage Rating And Type Per Function:

130.0 volts ac blank and 400.0 volts dc blank

Thread Size:

0.625 inches

Body Material:

Metal

Unpackaged Unit Weight:

9.000 ounces

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0