## NSN 5915-00-169-3576

Band Pass Filter - Page 1 of 2

3.50 kilohertz blank and 11.50 kilohertz blank



View Online at https://aerobasegroup.com/nsn/5915-00-169-3576

Overall Height:
6.440 inches
Body Length:
1.720 inches
Body Width:
1.350 inches
Body Height:
5.970 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.880 inches
Operating Tempurature Range:
+0.0 to 65.0 degrees celsius
Average Life Rating In Hours:
2000.0
Reference Frequency Per Function:
7.5 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank
Functional Terminal Type And Quantity:
1 turret output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
100.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
1.50 kilohertz blank and 3.50 kilohertz blank and 11.50 kilohertz blank and 15.00 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:

## NSN 5915-00-169-3576

Band Pass Filter - Page 2 of 2



<b>Discrimination At Speci</b>	ficationified Frequ	ıencies Per Fu	ınction In Decibels:
--------------------------------	---------------------	----------------	----------------------

60.0 blank and 3.0 blank and 60.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A047b0