

View Online at <https://aerobasegroup.com/nsn/5915-00-170-9646>

Overall Height:

0.812 inches

Body Length:

2.734 inches

Body Width:

0.500 inches

Body Height:

0.578 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Reference Frequency Per Function:

448.0 kilohertz blank

Source Impedance Rating Per Function:

20.0 kilohms blank

Load Impedance Per Function:

20.0 kilohms blank

Principal Circuitry Type Per Function:

Mechanical blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at altitude

Specified Frequencies Of Discrimination Per Function:

446.00 kilohertz blank and 447.15 kilohertz blank and 449.65 kilohertz blank and 450.40 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

447.15 kilohertz blank and 449.65 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0