

View Online at <https://aerobasegroup.com/nsn/5915-00-172-3058>

Overall Height:

0.850 inches

Body Length:

1.650 inches

Body Width:

1.010 inches

Body Height:

0.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.400 inches

Vibration Resistance Range In Hertz:

+10.0 to 500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.800 inches

Operating Temperature Range:

-30.0 to 85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

6.5 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

6.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

5.50 kilohertz blank and 6.148 kilohertz blank and 6.861 kilohertz blank and 7.60 kilohertz blank

Frequency Band Width Per Function:

6.148 kilohertz blank and 6.861 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0