

View Online at https://aerobasegroup.com/nsn/5915-00-190-4745

Overall Length:         0.882 inches         Body Length:         0.270 inches         Body Outside Diameter:         0.406 inches         Vibration Resistance Range In Hertz:         +10.0 to 2000.0         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Average Life Rating In Hours:         1000.0         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Operating Current Rating Per Function In Amps:         10.0 blank         Maximum Voltage Drop Per Function:         0.01 millivolts dc blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         28.0 volts dc blank
Body Length:         0.270 inches         Body Outside Diameter:         0.406 inches         Vibration Resistance Range In Hertz:         +10.0 to 2000.0         Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Average Life Rating In Hours:         1000.0         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Doperating Current Rating Per Function In Amps:         10.0 blank         Maximum Voltage Drop Per Function:         0.01 millivolts dc blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         28.0 volts dc blank
0.270 inches Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0 to 2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: -55.0/+125.0 degrees celsius Average Life Rating In Hours: -000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Load Impedance Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0 to 2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Doperating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
0.406 inches Vibration Resistance Range In Hertz: +10.0 to 2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Vibration Resistance Range In Hertz: +10.0 to 2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Load Impedance Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
+10.0 to 2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Operating Tempurature Range:         -55.0/+125.0 degrees celsius         Average Life Rating In Hours:         1000.0         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Operating Current Rating Per Function In Amps:         10.0 blank         Maximum Voltage Drop Per Function:         0.01 millivolts dc blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Inclosure Type:         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         28.0 volts dc blank
<ul> <li>-55.0/+125.0 degrees celsius</li> <li>Average Life Rating In Hours:</li> <li>1000.0</li> <li>Source Impedance Rating Per Function:</li> <li>50.0 ohms blank</li> <li>Load Impedance Per Function:</li> <li>50.0 ohms blank</li> <li>Operating Current Rating Per Function In Amps:</li> <li>10.0 blank</li> <li>Maximum Voltage Drop Per Function:</li> <li>0.01 millivolts dc blank</li> <li>Principal Circuitry Type Per Function:</li> <li>Inductance-capacitance blank</li> <li>Mounting Facility Screw Thread Series Designator:</li> <li>Unf</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>28.0 volts dc blank</li> </ul>
Average Life Rating In Hours: 1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 10.0 blank Maximum Voltage Drop Per Function: 10.0 1 millivolts de blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts de blank
1000.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Operating Current Rating Per Function In Amps:10.0 blankMaximum Voltage Drop Per Function:0.01 millivolts dc blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:28.0 volts dc blank
<ul> <li>10.0 blank</li> <li>Maximum Voltage Drop Per Function:</li> <li>0.01 millivolts dc blank</li> <li>Principal Circuitry Type Per Function:</li> <li>Inductance-capacitance blank</li> <li>Mounting Facility Screw Thread Series Designator:</li> <li>Unf</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>28.0 volts dc blank</li> </ul>
Maximum Voltage Drop Per Function: 0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
0.01 millivolts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Principal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:28.0 volts dc blank
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 28.0 volts dc blank
<ul> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>28.0 volts dc blank</li> </ul>
<ul> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>28.0 volts dc blank</li> </ul>
<b>Operating Voltage Rating And Type Per Function:</b> 28.0 volts dc blank
28.0 volts dc blank
Thread Size:
0.250 inches
Maximum Dielectric Withstanding Dc Voltage:
56.0 volts at sea level
Style Designator:
Style Designator: Round terminal/terminals on opposite surfaces
Round terminal/terminals on opposite surfaces

---

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0