

View Online at <https://aerobasegroup.com/nsn/5915-00-191-2430>

**Overall Height:**

0.960 inches

**Body Length:**

1.625 inches

**Body Width:**

0.885 inches

**Body Height:**

0.760 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.312 inches

**Vibration Resistance Range In Hertz:**

+10.0 to 55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.437 inches

**Operating Temperature Range:**

-40.0 to 80.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.981 megahertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.97975 megahertz blank and 1.9809 megahertz blank and 1.9811 megahertz blank and 1.98225 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.9809 megahertz blank and 1.9811 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

80.0 blank and 1.0 blank and 1.0 blank and 80.0 blank

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0