NSN 5915-00-200-9911

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-200-9911

| Overall Height: |
|---|
| 2.950 inches |
| Body Length: |
| 5.700 inches |
| Body Width: |
| 3.170 inches |
| Body Height: |
| 2.450 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 5.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.500 inches |
| Operating Tempurature Range: |
| +0.0/+50.0 degrees celsius |
| Reference Frequency Per Function: |
| 96.125 kilohertz blank |
| Source Impedance Rating Per Function: |
| 10.0 kilohms blank |
| Load Impedance Per Function: |
| 10.0 kilohms blank |
| Principal Circuitry Type Per Function: |
| Crystal blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 6.0 blank |
| Functional Terminal Type And Quantity: |
| 2 pin output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 92.50 kilohertz blank and 99.75 kilohertz blank and 100.25 kilohertz blank and 110.00 kilohertz blank |
| Thread Size: |
| 0.164 inches |
| Frequency Band Width Per Function: |
| 92.50 kilohertz blank and 99.75 kilohertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank |
| |

otyle Designator.

Rectangular terminal/terminals on one surface

NSN 5915-00-200-9911

Low Pass Filter - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0