

View Online at https://aerobasegroup.com/nsn/5915-00-205-2615

Overall Length: 1.102 inches Body Length: 0.560 inches Body Outside Diameter: 0.416 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function:
Body Length: 0.560 inches Body Outside Diameter: 0.416 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
0.560 inches Body Outside Diameter: 0.416 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Body Outside Diameter: 0.416 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
0.416 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Vibration Resistance Range In Hertz: +10.0/+500.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
+10.0/+500.0 <b>Operating Tempurature Range:</b> -55.0/+85.0 degrees celsius <b>Source Impedance Rating Per Function:</b> 50.0 ohms blank
Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
-55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank
Source Impedance Rating Per Function: 50.0 ohms blank
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
1.0 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
100.0 volts dc blank
Thread Size:
0.250 inches
Maximum Dielectric Withstanding Dc Voltage:
250.0 volts at sea level
Special Features:
Inductor at mounting end
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5915-00-205-2615

Radio Frequency Interference Filter - Page 2 of 2

**Fiig:** A047b0

