

View Online at <https://aerobasegroup.com/nsn/5915-00-208-4501>

Overall Height:

0.733 inches

Body Length:

3.000 inches

Body Width:

0.500 inches

Body Height:

0.515 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

27.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

2.0 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

6.75 megahertz blank and 24.00 megahertz blank and 30.00 megahertz blank and 61.00 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

24.00 megahertz blank and 30.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 1.0 blank and 1.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

24.0 megahertz blank and 30.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0