NSN 5915-00-220-9912

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-220-9912

| Overall Height: |
|---|
| 2.000 inches |
| Body Length: |
| 1.688 inches |
| Body Width: |
| 1.188 inches |
| Body Height: |
| 1.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Reference Frequency Per Function: |
| 745.0 hertz blank |
| Source Impedance Rating Per Function: |
| 10.0 kilohms blank |
| Load Impedance Per Function: |
| 10.0 kilohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 2.0 blank |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 525.00 hertz blank and 1.05 kilohertz blank and 1.596 kilohertz blank and 2.128 kilohertz blank |
| Thread Size: |
| 0.138 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 525.00 hertz blank and 1.05 kilohertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 3.0 blank and 3.0 blank and 30.0 blank and 45.0 blank |
| Style Designator: |

N/a

Shelf Life:

Rectangular terminal/terminals on one surface

NSN 5915-00-220-9912

Low Pass Filter - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A047b0