

View Online at <https://aerobasegroup.com/nsn/5915-00-226-3403>

Overall Length:

3.125 inches

Overall Height:

1.094 inches

Overall Width:

2.125 inches

Body Length:

3.125 inches

Body Width:

1.875 inches

Body Height:

Between 1.031 inches and 1.093 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.625 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

50.0 hertz blank

Source Impedance Rating Per Function:

1.8 ohms blank

Load Impedance Per Function:

140.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

20.00 hertz blank and 100.00 hertz blank and 500.00 hertz blank and 800.00 hertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

20.00 hertz blank and 100.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 23.00 blank and 45.0 blank and 45.0 blank

Body Surface Treatment:

Tin

Special Features:

Terminals on one surface

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

13499-673-0973-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0