

View Online at <https://aerobasegroup.com/nsn/5915-00-226-6862>

Overall Length:

6.188 inches

Body Length:

Between 4.063 inches and 4.187 inches

Body Outside Diameter:

Between 1.313 inches and 1.437 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Average Life Rating In Hours:

250.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

15.0 blank and 15.0 blank

Maximum Voltage Drop Per Function:

500.0 millivolts ac blank and 500.0 millivolts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 threaded stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 400.0 volts dc blank

Thread Size:

0.750 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Tin

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0