

View Online at <https://aerobasegroup.com/nsn/5915-00-232-2942>

Overall Length:

4.969 inches

Body Length:

Between 3.190 inches and 3.310 inches

Body Width:

Between 2.063 inches and 2.187 inches

Body Height:

Between 2.188 inches and 2.312 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.859 inches and 3.891 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

30.0 blank

Maximum Voltage Drop Per Function:

500.0 millivolts ac blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

1 threaded stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

150.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 400.0 volts dc blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

81349-milf15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milf15733/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0