

View Online at <https://aerobasegroup.com/nsn/5915-00-235-3588>

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

4.8 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

8.5 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

1.0 kilovolts at sea level

Specified Frequencies Of Discrimination Per Function:

3.60 kilohertz blank and 4.752 kilohertz blank and 4.848 kilohertz blank and 6.00 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

4.752 kilohertz blank and 4.848 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 8.5 blank and 8.5 blank and 20.0 blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0