NSN 5915-00-235-8863

Radio Frequency Interference Filter - Page 1 of 1



| 1.258 inches Body Outside Diameter: 0.416 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Operating Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | |
|--|---|
| 1.258 inches Body Outside Diameter: 0.416 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Operating Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | View Online at https://aerobasegroup.com/nsn/5915-00-235-8863 |
| Body Outside Diameter: 0.416 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Overall Length: |
| Operating Tempurature Range: -0.55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | 1.258 inches |
| Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Body Outside Diameter: |
| Source Impedance Rating Per Function: 55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | 0.416 inches |
| Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Operating Tempurature Range: |
| Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | -55.0/+85.0 degrees celsius |
| Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Source Impedance Rating Per Function: |
| Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | 50.0 ohms blank |
| Operating Current Rating Per Function In Amps: 0.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Load Impedance Per Function: |
| O.1 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | 50.0 ohms blank |
| Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Operating Current Rating Per Function In Amps: |
| Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | 0.1 blank |
| Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Principal Circuitry Type Per Function: |
| Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Inductance-capacitance blank |
| Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Mounting Facility Screw Thread Series Designator: |
| Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Unf |
| Mounting Facility Type And Quantity: 1 threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Inclosure Type: |
| Threaded bushing Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Hermetically sealed |
| Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Mounting Facility Type And Quantity: |
| Nut and washer Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | 1 threaded bushing |
| Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Features Provided: |
| 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Nut and washer |
| Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Functional Terminal Type And Quantity: |
| Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | 1 tab, solder lug output 2nd function |
| Thread Size: 0.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: | Operating Voltage Rating And Type Per Function: |
| D.250 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | 50.0 volts dc blank |
| Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Thread Size: |
| Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | 0.250 inches |
| Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Body Material: |
| Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: | Metal |
| Shelf Life: N/a Unit Of Measure: Demilitarization: | Style Designator: |
| N/a Unit Of Measure: Demilitarization: | Round terminal/terminals on opposite surfaces |
| Unit Of Measure: Demilitarization: | Shelf Life: |
| Demilitarization: | N/a |
| | Unit Of Measure: |
| | . |
| Yes - demil/mli | Demilitarization: |
| | Yes - demil/mli |

Fiig:

A047b0