

View Online at <https://aerobasegroup.com/nsn/5915-00-236-2153>

**Overall Height:**

Between 0.998 inches and 1.072 inches

**Body Length:**

Between 2.689 inches and 2.719 inches

**Body Width:**

Between 0.955 inches and 1.005 inches

**Body Height:**

Between 0.748 inches and 0.775 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.190 inches and 2.210 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.390 inches and 0.400 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

564.542 kilohertz blank

**Source Impedance Rating Per Function:**

1.0 kilohms blank

**Load Impedance Per Function:**

1.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Inclosure Type:**

Hermetically sealed

**Insertion Loss At Reference Frequency Per Function In Decibels:**

7.0 blank

**Specified Frequencies Of Discrimination Per Function:**

561.265 kilohertz blank and 563.200 kilohertz blank and 565.585 kilohertz blank and 567.819 kilohertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

563.200 kilohertz blank and 565.585 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

50.0 blank and 6.0 blank and 6.0 blank and 50.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0