

View Online at <https://aerobasegroup.com/nsn/5915-00-236-2154>

Overall Height:

Between 0.998 inches and 1.097 inches

Body Length:

Between 2.689 inches and 2.719 inches

Body Width:

Between 0.470 inches and 0.535 inches

Body Height:

Between 0.748 inches and 0.800 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.495 inches and 1.505 inches

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

566.445 kilohertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

565.84 kilohertz blank and 566.37 kilohertz blank and 566.52 kilohertz blank and 566.90 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

566.37 kilohertz blank and 566.52 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0