

View Online at <https://aerobasegroup.com/nsn/5915-00-236-2154>

**Overall Height:**

Between 0.998 inches and 1.097 inches

**Body Length:**

Between 2.689 inches and 2.719 inches

**Body Width:**

Between 0.470 inches and 0.535 inches

**Body Height:**

Between 0.748 inches and 0.800 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.495 inches and 1.505 inches

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

566.445 kilohertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

50.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

565.84 kilohertz blank and 566.37 kilohertz blank and 566.52 kilohertz blank and 566.90 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

566.37 kilohertz blank and 566.52 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0