## NSN 5915-00-237-2626

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-237-2626

Overall Height:
2.875 inches
Body Length:
1.688 inches
Body Width:
1.188 inches
Body Height:
2.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
230.0 hertz blank
Input Impedance Per Function W/load:
10.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
87.00 hertz blank and 175.00 hertz blank and 285.00 hertz blank and 570.00 hertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:

175.00 hertz blank and 285.00 hertz blank

# NSN 5915-00-237-2626

Band Pass Filter - Page 2 of 2



#### Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 4.0 blank and 4.0 blank and 30.0 blank

#### Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A047b0