NSN 5915-00-237-6175

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-237-6175

Overall Length:
2.000 inches
Body Width:
0.500 inches
Body Height:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.136 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.046 inches
Operating Tempurature Range:
-54.0/+110.0 degrees celsius
Reference Frequency Per Function:
775.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.4 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
1 connector, plug output 2nd function
Specified Frequencies Of Discrimination Per Function:
450.00 megahertz blank and 1.10 gigahertz blank and 2.00 gigahertz blank and 4.10 gigahertz blank
Body Material:
Metal
Frequency Band Width Per Function:
450.00 megahertz blank and 1.10 gigahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank
Voltage Standing Wave Ratio Frequency Limits Per Function:

Unpackaged Unit Weight:

2.000 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

450.0 megahertz blank and 1.1 gigahertz blank

NSN 5915-00-237-6175

Low Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0