

View Online at <https://aerobasegroup.com/nsn/5915-00-238-2968>

Overall Height:

1.250 inches

Body Length:

1.750 inches

Body Width:

0.750 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

100000.0

Reference Frequency Per Function:

52.4576 megahertz blank

Input Impedance Per Function W/load:

100.0 ohms blank

Output Impedance Per Function W/source Across Input:

100.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 wire hook output 2nd function

Specified Frequencies Of Discrimination Per Function:

52.4376 megahertz blank and 52.4526 megahertz blank and 52.4626 megahertz blank and 52.4776 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

52.4526 megahertz blank and 52.4626 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0