

View Online at <https://aerobasegroup.com/nsn/5915-00-239-0716>

**Overall Height:**

2.375 inches

**Body Length:**

0.750 inches

**Body Width:**

0.750 inches

**Body Height:**

2.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.500 inches

**Vibration Resistance Range In Hertz:**

+5.0/+33.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.500 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Reference Frequency Per Function:**

29.5 megahertz blank

**Source Impedance Rating Per Function:**

2.0 kilohms blank

**Load Impedance Per Function:**

2.0 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

3 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 wire hook output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

26.46 megahertz blank and 26.48 megahertz blank and 26.52 megahertz blank and 26.54 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

26.48 megahertz blank and 26.52 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0