

View Online at https://aerobasegroup.com/nsn/5915-00-242-3480

Overall Length:
2.504 inches
Overall Height:
1.125 inches
Body Length:
2.010 inches
Body Width:
2.010 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+95.0 degrees celsius
Power Line Frequency Rating Per Function In Hertz:
400.0 4th radio interference
Operating Current Rating Per Function In Amps:
0.8 4th radio interference
Maximum Voltage Drop Per Function:
1.0 volts ac 4th radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 3rd radio interference
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Inclosure Type: Hermetically sealed
Hermetically sealed
Hermetically sealed Mounting Facility Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function Thread Size:
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 0.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator:
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: a. 30.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: a) volts ac 3rd radio interference 3rd function Thread Size: a) 112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life:
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: a. 30.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a
 Hermetically sealed Mounting Facility Type And Quantity: threaded hole Functional Terminal Type And Quantity: tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: a. 30.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: No
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded hole Functional Terminal Type And Quantity: 4 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 130.0 volts ac 3rd radio interference 3rd function Thread Size: 0.112 inches Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: