## NSN 5915-00-243-1712

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-243-1712

Occasil Height
Overall Height:
6.440 inches
Body Length:
2.220 inches
Body Width:
1.350 inches
Body Height:
5.970 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.750 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.880 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
38.0 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
4.5 blank
Functional Terminal Type And Quantity:
2 turret input 1st function
Maximum Dielectric Withstanding Ac Rms Voltage:
100.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
27.00 kilohertz blank and 33.875 kilohertz blank and 42.125 kilohertz blank and 49.00 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:

33.875 kilohertz blank and 42.125 kilohertz blank

## NSN 5915-00-243-1712

Band Pass Filter - Page 2 of 2



80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0