NSN 5915-00-243-1724

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-243-1724

Overall Height:
6.380 inches
Body Length:
2.312 inches
Body Width:
1.625 inches
Body Height:
6.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.625 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
40.0 kilohertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
10.0 blank
Functional Terminal Type And Quantity:
1 turret output 2nd function
Specified Frequencies Of Discrimination Per Function:
36.50 kilohertz blank and 39.25 kilohertz blank and 40.75 kilohertz blank and 44.00 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:
39.25 kilohertz blank and 40.75 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

NSN 5915-00-243-1724

Band Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0