NSN 5915-00-256-4442

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-256-4442

Overall Length: 5.750 inches Body Length: 4.250 inches Body Width: 1.620 inches Body Height: 2.000 inches Body Height: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function W/source Across Input: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 30.0 ohms blank Voltage Standing Wave Ratio Per Function: 3.1 blank Inclosure Type: Encesed
Body Length: 4.250 inches Body Width: 1.620 inches Body Height: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 50.0 ohms blank Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 1.3 blank
4.250 inches Body Width: 1.620 inches Body Height: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Vutage Standing Wave Ratio Per Function: 51.0 ohms blank Vutage Standing Wave Ratio Per Function: 1.3 blank Holosure Type: Encased
Body Widh: 1.620 inches Body Height: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Input Impedance Per Function Wioad: 50.0 ohms blank Output Impedance Per Function Wioau: 50.0 ohms blank Vutage Standing Wave Ratio Per Function: 50.0 ohms blank Vutage Standing Wave Ratio Per Function: 50.0 ohms blank Vutage Standing Wave Ratio Per Function: 1.3 blank Helosure Type: Encased
1.620 inches Body Height: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+200.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Input Impedance Per Function Wload: 50.0 ohms blank Output Impedance Per Function Wload: 50.0 ohms blank Output Impedance Per Function Wload: 50.0 ohms blank Output Impedance Per Function Wload: 50.0 ohms blank Votage Standing Wave Ratio Per Function: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 50.1 ohms blank
Body Heigh: 2.000 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+200.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Input Impedance Per Function W/oad: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Vottage Standing Wave Ratio Per Function: 50.0 ohms blank Vottage Standing Wave Ratio Per Function: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 50.0 ohms blank Potage Standing Wave Ratio Per Function: 50.1 ohms blank Potage Standing Wave Ratio Per Function: 50.1 ohms blank
2.00 inches Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Lead Impedance Per Function 50.0 ohms blank Input Impedance Per Function Wload: 50.0 ohms blank Uutput Impedance Per Function Wload: 50.0 ohms blank Votage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Unthreaded Mounting Hole Diameter: 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Cutput Impedance Per Function W/load: 50.0 ohms blank Hotoge Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
3.750 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function Wiload: 50.0 ohms blank Input Impedance Per Function Wiload: 50.0 ohms blank Output Impedance Per Function Wiload: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
+10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
1.620 inches Operating Tempurature Range: -54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Operating Tempurature Range:-54.0/+70.0 degrees celsiusReference Frequency Per Function:312.0 megahertz blankSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankInput Impedance Per Function W/load:50.0 ohms blankOutput Impedance Per Function W/load:50.0 ohms blankInput Impedance Per Function W/load:50.0 ohms blankInput Impedance Per Function W/load:50.0 ohms blankOutput Impedance Per Function W/source Across Input:50.0 ohms blankInclosure Type:Encased
-54.0/+70.0 degrees celsius Reference Frequency Per Function: 312.0 megahertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Reference Frequency Per Function:312.0 megahertz blankSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankInput Impedance Per Function W/load:50.0 ohms blankOutput Impedance Per Function W/source Across Input:50.0 ohms blankInput Impedance Per Function W/source Across Input:50.0 ohms blankInclosure Standing Wave Ratio Per Function:1.3 blankInclosure Type:Encased
312.0 megahertz blankSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankInput Impedance Per Function W/load:50.0 ohms blankOutput Impedance Per Function W/source Across Input:50.0 ohms blankVoltage Standing Wave Ratio Per Function:1.3 blankInclosure Type:Encased
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Load Impedance Per Function: 50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
50.0 ohms blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Output Impedance Per Function W/source Across Input: 50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
50.0 ohms blank Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
Voltage Standing Wave Ratio Per Function: 1.3 blank Inclosure Type: Encased
1.3 blank Inclosure Type: Encased
Inclosure Type: Encased
Encased
Manufactory Excellent Trans And Oraci (*
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
1 connector, receptacle input 1st function
Frequency Band Width Per Function:
225.00 megahertz blank and 400.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
0.5 blank and 3.0 blank and 40.0 blank and 40.0 blank

NSN 5915-00-256-4442

Low Pass Filter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0

