

View Online at <https://aerobasegroup.com/nsn/5915-00-258-0031>

Overall Height:

1.500 inches

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.562 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

4.0 kilohertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 8.00 kilohertz blank and 12.00 kilohertz blank and 16.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

0.00 hertz blank and 8.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 30.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0