NSN 5915-00-262-3217

Radio Frequency Interference Filter - Page 1 of 1



-262-3217

| View Online at https://aerobasegroup.com/nsn/5915-00- |
|---|
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Power Line Frequency Rating Per Function In Hertz: |
| 400.0 4th radio interference |
| Operating Current Rating Per Function In Amps: |
| 2.0 4th radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 3rd radio interference |
| Input Terminal Manufacturer Code: |
| 96214 |
| Input Terminal Identification: |
| 535221-1 |
| Output Terminal Manufacturer Code: |
| 71468 |
| Output Terminal Identification: |
| Dpxbme26-34p5001 |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Functional Terminal Type And Quantity: |
| 1 connector, receptacle output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 125.0 volts ac 1st radio interference 1st function |
| Body Material: |
| Metal |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Vas - demil/mli |

Fiig:

A047b0