

View Online at <https://aerobasegroup.com/nsn/5915-00-263-0062>

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Reference Frequency Per Function:**

4.7 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

01238

**Input Terminal Identification:**

Cpr-187g

**Output Terminal Manufacturer Code:**

01238

**Output Terminal Identification:**

Cpr-187g

**Voltage Standing Wave Ratio Per Function:**

1.1 blank

**Average Power Rating Per Function:**

1.0 watts blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 flange

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.2 blank

**Functional Terminal Type And Quantity:**

1 rectangular flange output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

2.35 gigahertz blank and 4.40 gigahertz blank and 5.00 gigahertz blank and 9.40 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

4.40 gigahertz blank and 5.00 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

45.0 blank and 1.0 blank and 1.0 blank and 45.0 blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0