

View Online at <https://aerobasegroup.com/nsn/5915-00-270-4789>

**Overall Length:**

1.138 inches

**Body Length:**

0.598 inches

**Body Outside Diameter:**

0.406 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

0.25 blank

**Maximum Voltage Drop Per Function:**

0.8 volts dc blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.03 and 0.15 and 0.3 and 1.0 and 10.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

20.0 and 50.0 and 60.0 and 74.0 and 74.0 and 74.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

80.0 volts dc blank

**Thread Size:**

0.250 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

160.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Capacitor at mounting end

**Unpackaged Unit Weight:**

6.0 grams

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0