NSN 5915-00-274-2259

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-274-2259

Overall Length:
2.500 inches
Overall Height:
0.350 inches
Body Length:
1.500 inches
Body Width:
0.700 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.100 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Reference Frequency Per Function:
16.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Specified Frequencies Of Discrimination Per Function:
2.00 megahertz blank and 30.00 megahertz blank and 79.00 megahertz blank and 200.00 megahertz blank
Body Material:
Metal
Frequency Band Width Per Function:
2.00 megahertz blank and 30.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
0.5 blank and 0.5 blank and 50.0 blank and 50.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

NSN 5915-00-274-2259

Low Pass Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0