

View Online at <https://aerobasegroup.com/nsn/5915-00-275-2141>

Overall Height:

2.656 inches

Body Length:

1.719 inches

Body Width:

1.219 inches

Body Height:

2.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Reference Frequency Per Function:

25.0 kilohertz blank

Source Impedance Rating Per Function:

5.0 kilohms blank

Load Impedance Per Function:

5.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 kilohertz blank and 25.00 kilohertz blank and 410.00 kilohertz blank and 820.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 kilohertz blank and 25.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 30.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0