NSN 5915-00-278-4198

Band Suppression Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-278-4198

Overall Height:
2.203 inches
Body Length:
2.000 inches
Body Width:
1.385 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.600 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Operating Tempurature Range:
-30.0/+65.0 degrees celsius
Reference Frequency Per Function:
2.74 megahertz blank
Input Impedance Per Function W/load:
75.0 ohms blank
Output Impedance Per Function W/source Across Input:
75.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Hermetically sealed Mounting Facility Type And Quantity:
-
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole
Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.5 blank
Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.5 blank Functional Terminal Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.5 blank Functional Terminal Type And Quantity: 2 pin output 2nd function
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blank
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inches
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:
Mounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:Metal
Nounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:MetalFrequency Band Width Per Function:
Nounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:MetalFrequency Band Width Per Function:2.70 megahertz blank and 2.78 megahertz blank and 2.78 megahertz blank
Nounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:MetalFrequency Band Width Per Function:2.70 megahertz blank and 2.78 megahertz blankDiscrimination At Specificationified Frequencies Per Function In Decibels:
Nounting Facility Type And Quantity:2 threaded holeInsertion Loss At Reference Frequency Per Function In Decibels:1.5 blankFunctional Terminal Type And Quantity:2 pin output 2nd functionSpecified Frequencies Of Discrimination Per Function:2.60 megahertz blank and 2.70 megahertz blank and 2.78 megahertz blank and 3.18 megahertz blankThread Size:0.138 inchesBody Material:MetalFrequency Band Width Per Function:2.70 megahertz blank and 2.78 megahertz blankDiscrimination At Specificationified Frequencies Per Function In Decibels:1.0 blank and 50.0 blank and 50.0 blank and 1.0 blank

NSN 5915-00-278-4198

Band Suppression Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

13499-241-0499-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0