

View Online at <https://aerobasegroup.com/nsn/5915-00-281-0265>

Overall Height:

2.969 inches

Body Length:

6.031 inches

Body Width:

1.438 inches

Body Height:

2.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Operating Temperature Range:

-65.0/+150.0 degrees celsius

Reference Frequency Per Function:

83.0 kilohertz blank

Input Impedance Per Function W/load:

135.0 ohms blank

Output Impedance Per Function W/source Across Input:

135.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.7 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

64.00 kilohertz blank and 76.50 kilohertz blank and 91.00 kilohertz blank and 120.00 kilohertz blank

Thread Size:

0.190 inches

Frequency Band Width Per Function:

76.50 kilohertz blank and 91.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 6.7 blank and 6.2 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0