

View Online at <https://aerobasegroup.com/nsn/5915-00-281-0304>

**Overall Height:**

2.969 inches

**Body Length:**

6.031 inches

**Body Width:**

1.438 inches

**Body Height:**

2.594 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.812 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.938 inches

**Operating Temperature Range:**

-65.0/+185.0 degrees fahrenheit

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

54.5 kilohertz blank

**Input Impedance Per Function W/load:**

240.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

240.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 kilohertz blank and 108.00 kilohertz blank and 120.00 kilohertz blank and 400.00 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 kilohertz blank and 108.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

2.5 blank and 2.5 blank and 55.0 blank and 55.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0