

View Online at <https://aerobasegroup.com/nsn/5915-00-281-0304>

Overall Height:

2.969 inches

Body Length:

6.031 inches

Body Width:

1.438 inches

Body Height:

2.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.812 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Operating Temperature Range:

-65.0/+185.0 degrees fahrenheit

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

54.5 kilohertz blank

Input Impedance Per Function W/load:

240.0 ohms blank

Output Impedance Per Function W/source Across Input:

240.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 kilohertz blank and 108.00 kilohertz blank and 120.00 kilohertz blank and 400.00 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 kilohertz blank and 108.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

2.5 blank and 2.5 blank and 55.0 blank and 55.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0