NSN 5915-00-283-1146

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-283-1146

Overall Height:

0.931 inches

Body Length:

Between 2.281 inches and 2.343 inches

Body Width:

Between 1.406 inches and 1.468 inches

Body Height:

0.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Tempurature Range:

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

2.0 kilohertz blank

Source Impedance Rating Per Function:

5.0 kilohms blank

Load Impedance Per Function:

5.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 8.00 kilohertz blank and 16.00 kilohertz blank and 20.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

0.00 hertz blank and 8.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.0 blank and 25.0 blank and 56.0 blank and 71.0 blank

NSN 5915-00-283-1146

Low Pass Filter - Page 2 of 2



Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0