## NSN 5915-00-283-1146

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-283-1146

**Overall Height:** 

0.931 inches

**Body Length:** 

Between 2.281 inches and 2.343 inches

**Body Width:** 

Between 1.406 inches and 1.468 inches

**Body Height:** 

0.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

**Operating Tempurature Range:** 

-55.0/+65.0 degrees celsius

**Average Life Rating In Hours:** 

2000.0

**Reference Frequency Per Function:** 

2.0 kilohertz blank

**Source Impedance Rating Per Function:** 

5.0 kilohms blank

**Load Impedance Per Function:** 

5.0 kilohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:** 

Unc

Inclosure Type:

Encased

**Mounting Facility Type And Quantity:** 

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

**Functional Terminal Type And Quantity:** 

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:** 

0.00 hertz blank and 8.00 kilohertz blank and 16.00 kilohertz blank and 20.00 kilohertz blank

**Thread Size:** 

0.112 inches

**Frequency Band Width Per Function:** 

0.00 hertz blank and 8.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.0 blank and 25.0 blank and 56.0 blank and 71.0 blank

## NSN 5915-00-283-1146

Low Pass Filter - Page 2 of 2



Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0