

View Online at https://aerobasegroup.com/nsn/5915-00-287-5062

| Overall Length: 5.072 inches Body Length: 4.250 inches Body Outside Diameter: 1.500 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 25.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
|--|
| Body Length: 4.250 inches Body Outside Diameter: 1.500 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 4.250 inches Body Outside Diameter: 1.500 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: |
| Body Outside Diameter: 1.500 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function In Amps: 2.0 blank Poincipal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 1.500 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Funced Size: 0.750 inches Body Material: Metal |
| Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Operating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:2.0 blankPrincipal Circuitry Type Per Function:Capacitance-inductance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:125.0 volts ac blankThread Size:0.750 inchesBody Material:Metal |
| -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function In Amps: 2.0 blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 the, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Power Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:2.0 blankPrincipal Circuitry Type Per Function:Capacitance-inductance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:125.0 volts ac blankThread Size:0.750 inchesBody Material:Metal |
| 400.0 blank Operating Current Rating Per Function In Amps: 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Operating Current Rating Per Function In Amps:2.0 blankPrincipal Circuitry Type Per Function:Capacitance-inductance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:125.0 volts ac blankThread Size:0.750 inchesBody Material:Metal |
| 2.0 blank Principal Circuitry Type Per Function: Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Principal Circuitry Type Per Function:Capacitance-inductance blankMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:125.0 volts ac blankThread Size:0.750 inchesBody Material:Metal |
| Capacitance-inductance blank Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Unef Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| 125.0 volts ac blank Thread Size: 0.750 inches Body Material: Metal |
| Thread Size: 0.750 inches Body Material: Metal |
| 0.750 inches Body Material: Metal |
| Body Material: Metal |
| Metal |
| |
| Special Features: |
| opecial realures. |
| Inductance at mounting end |
| Chula Designatory |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |
| |
| Round terminal/terminals on opposite surfaces |



Demilitarization:

No

Fiig:

A047b0