

View Online at <https://aerobasegroup.com/nsn/5915-00-287-9995>

Overall Height:

2.125 inches

Body Length:

3.500 inches

Body Height:

1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Reference Frequency Per Function:

30.7465 hercules no.5599.1 two phase to two phase

Input Impedance Per Function W/load:

50.0 ohms 2nd band pass

Output Impedance Per Function W/source Across Input:

50.0 ohms 1st band pass

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 3rd band pass

Functional Terminal Type And Quantity:

6 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

10.00 megahertz 2nd band pass 2nd function and 30.50 megahertz 2nd band pass 2nd function and 30.94 megahertz 2nd band pass 2nd function and 80.00 megahertz 2nd band pass 2nd function

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

30.50 megahertz 3rd band pass and 30.94 megahertz 3rd band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 1st band pass 1st function and 3.0 1st band pass 1st function and 3.0 1st band pass 1st function and 60.0 1st band pass 1st function

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0