NSN 5915-00-306-4090

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-306-4090

| Overall Height: |
|---|
| 2.500 inches |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 1.750 inches |
| Body Height: |
| 1.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 1.495 inches and 1.505 inches |
| Operating Tempurature Range: |
| -25.0/+71.0 degrees celsius |
| Reference Frequency Per Function: |
| 100.0 hertz blank |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 23.5 kilohms blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 6.0 blank |
| Functional Terminal Type And Quantity: |
| 1 wire lead input 1st function |
| Specified Frequencies Of Discrimination Per Function: |
| 15.00 hertz blank and 75.00 hertz blank and 125.00 hertz blank and 200.00 hertz blank |
| Thread Size: |
| 0.138 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 75.00 hertz blank and 125.00 hertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 3.0 blank and 30.0 blank |

Tin

Body Surface Treatment:

NSN 5915-00-306-4090

Band Pass Filter - Page 2 of 2



| Style | De | siar | nato | r |
|-------|----|-------|------|---|
| , | | v. 9. | | |

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0