## NSN 5915-00-306-4091

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-306-4091

Overall Height:
2.500 inches
Body Length:
2.000 inches
Body Width:
1.750 inches
Body Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.495 inches and 1.505 inches
Operating Tempurature Range:
-25.0/+71.0 degrees celsius
Reference Frequency Per Function:
200.0 hertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
23.5 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Hermetically sealed
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank
Unc Inclosure Type: Hermetically sealed Hounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank Thread Size:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank Thread Size: 0.138 inches
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank Thread Size: 0.138 inches Body Material:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank Thread Size: 0.138 inches Body Material: Metal
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 wire lead input 1st function Specified Frequencies Of Discrimination Per Function: 100.00 hertz blank and 175.00 hertz blank and 225.00 hertz blank and 300.00 hertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function:
Unc Inclosure Type: Inclosure Type: Inclosure Type: Inclosure Type: Inclosure Type: Inclosure Type And Quantity: Inclose At Reference Frequency Per Function In Decibels: Insertion Loss At Reference Frequency Per Function In Decibels: Inclosure Type And Quantity: Inclosure Type

## NSN 5915-00-306-4091

Band Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0