

View Online at <https://aerobasegroup.com/nsn/5915-00-306-4104>

Overall Height:

2.250 inches

Body Length:

1.500 inches

Body Width:

1.250 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-25.0/+71.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.7 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

23.5 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

7.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.60 kilohertz blank and 1.675 kilohertz blank and 1.725 kilohertz blank and 1.80 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.675 kilohertz blank and 1.725 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0