## NSN 5915-00-306-4105

Band Pass Filter - Page 1 of 2

Metal



View Online at https://aerobasegroup.com/nsn/5915-00-306-4105 **Overall Height:** 2.250 inches **Body Length:** 1.500 inches **Body Width:** 1.500 inches **Body Height:** 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.000 inches **Vibration Resistance Range In Hertz:** +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Operating Tempurature Range:** -25.0/+71.0 degrees celsius **Average Life Rating In Hours:** 10000.0 **Reference Frequency Per Function:** 440.0 hertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 23.5 kilohms blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: **Functional Terminal Type And Quantity:** 1 wire lead input 1st function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level **Specified Frequencies Of Discrimination Per Function:** 340.00 hertz blank and 415.00 hertz blank and 465.00 hertz blank and 540.00 hertz blank **Thread Size:** 0.138 inches **Body Material:** 

## NSN 5915-00-306-4105

Band Pass Filter - Page 2 of 2



Frequency	<b>Band</b>	Width	Per	Function:
-----------	-------------	-------	-----	-----------

415.00 hertz blank and 465.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

**Body Surface Treatment:** 

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0