# NSN 5915-00-306-4105

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-306-4105

## **Overall Height:** 2.250 inches **Body Length:** 1.500 inches **Body Width:** 1.500 inches **Body Height:** 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.000 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Operating Tempurature Range:** -25.0/+71.0 degrees celsius Average Life Rating In Hours: 10000.0 **Reference Frequency Per Function:** 440.0 hertz blank Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 23.5 kilohms blank Mounting Facility Screw Thread Series Designator: Unc **Inclosure Type:** Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank **Functional Terminal Type And Quantity:** 1 wire lead input 1st function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level **Specified Frequencies Of Discrimination Per Function:** 340.00 hertz blank and 415.00 hertz blank and 465.00 hertz blank and 540.00 hertz blank **Thread Size:** 0.138 inches **Body Material:** Metal

# NSN 5915-00-306-4105

Band Pass Filter - Page 2 of 2



#### **Frequency Band Width Per Function:**

415.00 hertz blank and 465.00 hertz blank

### Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

### Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A047b0