

View Online at https://aerobasegroup.com/nsn/5915-00-320-6989

Overall Length:1.192 inchesBody Length:0.540 inchesBody Outside Diameter:0.385 inchesVibration Resistance Range In Hertz:+10.0/+2000.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankOperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfIncosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts de blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:NaViat Of Measure:	
Body Length:0.540 inchesBody Outside Diameter:0.385 inchesVibration Resistance Range In Hertz:+10.0/+2000.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankOperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfIndesure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:10.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesSheff Life:N/a	Overall Length:
0.540 inchesBody Outside Diameter:0.385 inchesVibration Resistance Range In Hertz:+10.0/+2000.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankOperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per FunctionInductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts de blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:10.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesSheff Life:N/a	1.192 inches
Body Outside Diameter: 0.385 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Poerating Current Rating Per Function In Amps: 10.0 blank Porticipal Circuitry Type Per Function In Amps: 10.0 blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts de blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end <	Body Length:
NameNameVibration Resistance Range In Hertz:+10.0/+2000.0Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankDoperating Current Rating Per Function In Amps:10.0 blankPerincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Na	0.540 inches
Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function In Amps: 10.0 blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a 	Body Outside Diameter:
+10.0/+2000.0 Operating Tempurature Range: -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 10.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	0.385 inches
Operating Tempurature Range:-55.0/+125.0 degrees celsiusAverage Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankCoperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:10.0.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminals on opposite surfacesShelf Life:N/a	Vibration Resistance Range In Hertz:
 -55.0/+125.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Doperating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts de blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: N/a 	+10.0/+2000.0
Average Life Rating In Hours:250.0Source Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankOperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:10.0.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesShelf Life:N/a	Operating Tempurature Range:
250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: N/a	-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Average Life Rating In Hours:
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	250.0
Load Impedance Per Function:50.0 ohms blankOperating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesShelf Life:N/a	Source Impedance Rating Per Function:
50.0 ohms blank Operating Current Rating Per Function In Amps: 10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: N/a	50.0 ohms blank
Operating Current Rating Per Function In Amps:10.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts de blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:N/a	Load Impedance Per Function:
10.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	50.0 ohms blank
Principal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:EncasedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesShelf Life:N/a	Operating Current Rating Per Function In Amps:
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	10.0 blank
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Principal Circuitry Type Per Function:
Unf Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Inductance-capacitance blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Mounting Facility Screw Thread Series Designator:
Encased Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Unf
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Inclosure Type:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Encased
Functional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:50.0 volts dc blankThread Size:0.250 inchesMaximum Dielectric Withstanding Dc Voltage:100.0 volts at sea levelSpecial Features:Capacitor at mounting endStyle Designator:Round terminal/terminals on opposite surfacesShelf Life:N/a	Mounting Facility Type And Quantity:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	1 threaded bushing
Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Functional Terminal Type And Quantity:
50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	1 tab, solder lug output 2nd function
Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Operating Voltage Rating And Type Per Function:
0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	50.0 volts dc blank
Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Thread Size:
100.0 volts at sea level Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	0.250 inches
Special Features: Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Maximum Dielectric Withstanding Dc Voltage:
Capacitor at mounting end Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	100.0 volts at sea level
Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a	Special Features:
Round terminal/terminals on opposite surfaces Shelf Life: N/a	Capacitor at mounting end
Shelf Life: N/a	Style Designator:
N/a	Round terminal/terminals on opposite surfaces
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0